



Cast aluminium lever  
Lever with 9 positions  
Lockable lever 0/90°



Continuous, drained shaft  
(no mechanical play)



Dovetail (simplifies  
maintenance)



ISO flange for  
direct mounting

Epoxy coating RAL5012  
thickness 250-300 micron

**GENERAL FEATURES**



PN 3 - PN 6 - PN 10 - PN 16  
ANSI 150



**MATERIALS**

**BODY**

- GG 25
- GGG 40
- GGG 50
- Stainless steel 304
- Stainless steel 316
- Steel GS-C25
- Aluminium
- Bronze
- Other on request

**STEM**

- Stainless steel 304
- Stainless steel 316
- Stainless steel 420
- Hastelloy
- On request

**DISC**

- GG 25
- GGG 50
- Stainless steel 304
- Stainless steel 316
- Steel GS-C25
- Aluminium
- Bronze
- On request

**SEAT**

- EPDM
- Hypalon
- NBR
- Silicone
- PTFE
- Viton
- Silicone (food)
- Silicone (steam)
- EPDM (food)
- Viton (food)

**OPTIONS**

- pneumatic
- electric
- electro-pneumatic
- gearbox
- limit switches
- stem extension
- ...

**CERTIFICATES**

- 3.1
- CE
- PED
- ATEX
- FDA
- ISO 9001
- GOST-R



**SEATS**

**EPDM**  
-10 °C - +110 °C

**PTFE**  
-25 °C - +200 °C

**NBR**  
-10 °C - +90 °C




**Natural rubber**  
-10 °C - +90 °C

**EPDM high temperature**  
-10 °C - +130 °C

**Hypalon**  
-10 °C - +90 °C

**Silicone**  
-40 °C - +150 °C

**Viton**  
-5 °C - +180 °C

**2-PIECE BODY****LUG****GEARBOX****THROTTLE VALVE****DOUBLE FLANGED****AUTOMATION****INDUSTRY****FOOD INDUSTRY****PETROCHEMICAL****GAS****POSITION INDICATOR****POTABLE WATER****FIRE PROTECTION****3D DRAWINGS**